

The modern line models



Warm regards,



Modern Line		Price	Weight	Chimney Exit		Footprint		Wood Longth	Load per Firing	Max. Heat
						Width	Depth	Wood Length	Load per Filling	Output*
	Technical Information & Pricing	USD	lb	Тор	Base	in.	in.	in.	lb	Btu
Small Models 300 to 750 sq ft heated area (depending on heating requirements)										
TU1000/50	4 ft heater with mitred corners	\$6,300	2,200		В	33	19	10-11	18	9,500
TU1000T/50	5 ft heater with mitred corners	\$7,900	2,900	Т		33	19	10-11	23	12,000
TU1000/92	5 ft heater	\$7,600	2,700		В	33	19	10-11	22	11,500
TU1000T/92	5 ft heater	\$7,950	2,900	Т		33	19	10-11	23	12,000
Mid-Sized Models 500 to 1100 sq ft heated area (depending on heating requirements)										
TU2200/50	5 ft heater with mitred corners	\$8,700	3,900		В	40	24	14-15	31	16,500
TU2200T/50	5 ft heater with mitred corners	\$8,950	3,950	Т		40	24	14-15	32	16,000
TU2200/92	5 ft heater	\$8,500	3,900		В	40	24	14-15	31	16,500
TU2200T/92	5 ft heater	\$9,250	4,100	Т		40	24	14-15	33	16,500
TLU2000/50	5 ft 5 heater with 15.5" x 18.5" bakeoven	\$11,450	4,300		В	37	27	12-13	34	18,000
TLU2000/92	5 ft 5 heater with 15.5" x 18.5" bakeoven	\$11,850	4,250		В	37	27	12-13	34	18,000
TLU2000/94	5 ft 5 heater with 15.5" x 18.5" rear-facing bakeoven	\$12,150	4,350		В	37	27	12-13	35	18,000
Large Models 600 to 1500 sq ft heated area (depending on heating requirements)										
TTU2700/8 XL	6 ft heater	\$11,950	6,100	Т		40	30	14-18	49	23,500
TU2450/92	5 ft 6 heater with 17.5" x 22" bakeoven	\$14,550	5,950		В	43	35	14-15	48	23,500
	Optional Surface Finishes particularly suitable for /50 models									
Grafia or Nobile on small models		\$300								
Grafia or Nobile on mid-sized and large models		\$500								

^{*}Maximum heat output is based on two fires per day, at least 10 hours apart.

Measurements in inches are rounded; please refer to construction drawings for exact measurements in millimeters.

Delivery and on-site assembling are not included in Price. Heat shields, hearth tiles, benches & other accessories are available as optional features.

Tulikivi heaters require appropriate structural support. Being a naturally occuring material, soapstone can vary in aspect and weight.

5 years Warranty. Tulikivi heaters are UL/ULC safety tested & listed and must be assembled by a Tulikivi installer. EPA certification is not required.

Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise.

Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Can be reduced to 3" with a UL/ULC specified heat shield.

Floor protection: non-combustible material at least 3/8" thick, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front.



